

Collar Information							Grade Summary					
Hole ID	Easting (NAD 83 Zone 10)	Northing (NAD 83 Zone 10)	Elevation (m asl)	Depth (m)	Azimuth	Dip	Depth From (m)	Depth To (m)	Interval (m)	Au (g/t)	Ag (g/t)	Highest Au Assay in Reported Interval (g/t)
SNR26-110 and and	654897	5523606	1341	321.0	50	-46	159.42 206.00 264.00	165.40 243.34 270.00	5.98 37.34* 6.00	1.86 6.24 3.50	1.6 54.7 4.7	5.83 31.90 5.89
SNR26-111 and	654781	5523925	1338	323.0	60	-49	84.00 244.50	86.00 249.00	2.00 4.50	1.03 2.29	3.0 8.1	1.03 2.77
SNR26-112 and	654728	5523665	1322	379.5	51	-46	162.00 333.00	164.00 340.50	2.00 7.50	4.56 1.57	10.9 9.2	4.56 8.64
SNR26-115	654803	5523921	1346	393.8	60	-48	175.00	177.00	2.00	1.63	6.9	1.78
SNR26-117	654720	5523629	1322	448.5	51	-47	384.00	394.04	10.04	12.18	102.7	39.50
SNR26-118 and and	654812	5523967	1348	275.0	60	-48	33.00 42.60 178.70	35.00 47.00 183.50	2.00 4.40 4.80	1.20 1.50 2.20	4.1 6.5 3.0	1.20 1.65 3.74

Reported intervals are at least 2m in length with a 1 g/t Au cut-off for individual samples and no more than 3m contiguous metres dilution.

Or less than 2m in length with an individual sample returning >10 g/t Au.

*Reported interval includes 4.10 contiguous metres with assays <1 g/t Au.